Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: IDENTIFICATION

1.1. Product Identifier Product Form: Mixture

Product Name: Commercial High Speed (CHS) Tire Sealant

1.2. Intended Use of the Product Use of the Substance/Mixture: Tire Sealant

1.3. Name, Address, and Telephone of the Responsible Party

Company

Inovex Industries Inc

45681 Oakbrook Court, Unit 102

Sterling, VA 201166 USA

703-421-9778

1-888-374-3366 (US Only)

1.4. Emergency Telephone Number

Emergency Number : 1-800-255-3924 (24 hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Acute Tox. 4 (Oral) H302 STOT RE 2 H373

Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : H302 - Harmful if swallowed.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements (GHS-US) : P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P330 - Rinse mouth.

P501 - Dispose of contents/container in accordance with local, regional, national,

and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

JILI WINCON			
Name	Product Identifier	%	GHS-US classification
Ethylene glycol	(CAS-No.) 107-21-1	50 - 60	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Water	(CAS-No.) 7732-18-5	30 - 42	Not classified
Proprietary Component 1	(CAS-No.) Proprietary	0.8 - 1.3	Not classified

11/20/2017 EN (English US) 1/7

Safety Data Shee

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary Component 2	(CAS-No.) Proprietary	0.08 - 0.325	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402
Proprietary Component 3	(CAS-No.) Proprietary	0.0425 - 0.0625	Met. Corr. 1, H290 Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314 Eye Dam. 1, H318

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: This material is harmful orally and can cause adverse health effects or death in significant amounts.

Chronic Symptoms: Repeated or prolonged exposure may damage kidneys.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical. **Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

11/20/2017 EN (English US) 2/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. **Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Handle empty containers with care because they may still present a hazard. Do not get in eyes, on skin, or on clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Tire Sealant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or the Mexican government.

Proprietary Component 1			
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³	
Proprietary Component 2			
Mexico	OEL TWA (mg/m³)	50 mg/m ³	
Mexico	OEL TWA (ppm)	10 ppm	
USA ACGIH	ACGIH TWA (ppm)	2 ppm	
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the	
		cutaneous route	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	50 mg/m ³	
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm	
USA IDLH	US IDLH (ppm)	100 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm	
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption	
Proprietary C	Component 3		
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³	
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	2 mg/m³	
Ethylene glycol (107-21-1)			
Mexico	OEL Ceiling (mg/m³)	100 mg/m³ (aerosol)	
USA ACGIH	ACGIH TWA (ppm)	25 ppm (vapor fraction)	
USA ACGIH	ACGIH STEL (mg/m³)	10 mg/m³ (inhalable particulate matter, aerosol only)	
USA ACGIH	ACGIH STEL (ppm)	50 ppm (vapor fraction)	
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen	

11/20/2017 EN (English US) 3/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure Controls

Appropriate Engineering Controls : Suitable eye/body wash equipment should be available in the vicinity of any

potential exposure. Ensure adequate ventilation, especially in confined areas.

Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.







Materials for Protective Clothing

thing : Chemically resistant materials and fabrics.: Wear protective gloves.

Hand Protection

Eye and Face Protection

Skin and Body Protection

: Chemical safety goggles.

on : Wear suitable protective clothing.

Respiratory Protection : If exposure limits are exceeded or

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information : When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance: No data availableOdor: No data availableOdor Threshold: No data available

pH : 9.8 - 10.2

: No data available **Evaporation Rate Melting Point** : No data available **Freezing Point** : No data available **Boiling Point** : No data available **Flash Point** $: > 500 \, ^{\circ}\text{F} (260 \, ^{\circ}\text{C})$ **Auto-ignition Temperature** : No data available **Decomposition Temperature** : No data available Flammability (solid, gas) : Not applicable Vapor Pressure : No data available Relative Vapor Density at 20°C : No data available : No data available **Relative Density Specific Gravity** : 1.07-1.11

Solubility : No data available
Partition Coefficient: N-Octanol/Water : No data available
Viscosity : No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- **10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- **10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products: None expected under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Oral: Harmful if swallowed.

Auto/SUV Sealant, Commercial High Speed Sealant, Motorcycle Sealant		
ATE (Oral)	825.18 mg/kg body weight	

11/20/2017 EN (English US) 4/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary Component 1		
LD50 Oral Rat	6400 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
Proprietary Component 2		
LD50 Oral Rat	1320 mg/kg	
LD50 Dermal Rabbit	1 ml/kg	
LC50 Inhalation Rat	4.3 mg/l/4h	
ATE (Dermal)	300.00 mg/kg body weight	
Proprietary Component 3		
LD50 Oral Rat	284 mg/kg	
Ethylene glycol (107-21-1)		
LD50 Dermal Rat	10600 mg/kg	
ATE (Oral)	500.00 mg/kg body weight	

Skin Corrosion/Irritation: Not classified

pH: 9.8 - 10.2

Serious Eye Damage/Irritation: Not classified

pH: 9.8 - 10.2

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified Carcinogenicity: Not classified

Proprietary Component 1	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: This material is harmful orally and can cause adverse health effects or death in significant

amounts.

Chronic Symptoms: Repeated or prolonged exposure may damage kidneys.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Proprietary Component 1		
LC50 Fish 1	10600 (10600 - 13000) mg/l (Exposure time: 96 h - Species: Pimephales promelas	
	[flow-through])	
EC50 Daphnia 1	1386 mg/l	
LC50 Fish 2	1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
ErC50 (Algae)	169 mg/l	
NOEC Chronic Crustacea	16 mg/l	
Proprietary Component 2		
LC50 Fish 1	1660 - 1920 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-	
	through])	
EC50 Daphnia 1	83.6 mg/l (Exposure time: 48 h - Species: Daphnia magna Straus)	
ErC50 (Algae)	44 mg/l	
Ethylene glycol (107-21-1)		
LC50 Fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	
NOEC Chronic Crustacea	4.2 mg/l	

11/20/2017 EN (English US) 5/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and Degradability

Auto/SUV Sealant, Commercial High Speed Sealant, Motorcycle Sealant	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Auto/SUV Sealant, Commercial High Speed Sealant, Motorcycle Sealant		
Bioaccumulative Potential	Not established.	
Proprietary Component 1		
BCF Fish 1	3.9	
Log Pow	-2.53	
Proprietary Component 2		
Log Pow	0.21 (at 23 °C)	
Proprietary Component 3		
Log Pow	0.65	
Ethylene glycol (107-21-1)		
Log Pow	-1.93	

- **12.4. Mobility in Soil** No additional information available
- 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Auto/SUV Sealant, Commercial High Speed Sealant, Motorcycle Sealant		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
	Immediate (acute) health hazard	
Water (7732-18-5)		
Listed on the United States TSCA (Toxic Substances Contro	ol Act) inventory	
Proprietary Component 1		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Proprietary Component 2		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Proprietary Component 3		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	1000 lb	
Ethylene glycol (107-21-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Subject to reporting requirements of United States SARA Section 313		
CERCLA RQ	5000 lb	
SARA Section 313 - Emission Reporting	1%	

15.2. US State Regulations

Ethylene glycol (107-21-1)	
U.S California - Proposition 65 - Developmental	WARNING: This product contains chemicals known to the State of

11/20/2017 EN (English US) 6/7

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toxicity California to cause birth defects. Proprietary Component 1 U.S. - Massachusetts - Right To Know List

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Proprietary Component 2

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Proprietary Component 3

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Ethylene glycol (107-21-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 11/20/2017

 Other Information
 : This document has been prepared in accordance with the SDS

requirements of the OSHA Hazard Communication Standard 29 CFR

1910.1200

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)

11/20/2017 EN (English US) 7/7